


AD-A263 987



FASTC-ID(RS)T-0244-93

2

FOREIGN AEROSPACE SCIENCE AND TECHNOLOGY CENTER



METHOD OF DRYING POLYMER PAINT AND VARNISH COATINGS
ON METAL PARTS

(Description of an invention for an author's certificate)

by

M.D. Maksimenko, S.G. Romanovskiy, et al.



SDTIC
ELECTE
MAY 11 1993
S E D

Approved for public release;
Distribution unlimited.



93 5 06 06 5

93-09989



HUMAN TRANSLATION

FASTC-ID(RS)T-0244-93

20 April 1993

MICROFICHE NR: 93C000286

METHOD OF DRYING POLYMER PAINT AND VARNISH
COATINGS ON METAL PARTS
(Description of an invention for author's
certificate)

By: M.D. Maksimenko, S.G. Romanovskiy, et al.

English pages: 2

Source: Russian Patent Nr. 507755, 24 December 1971;
pp. 1-2

Country of origin: USSR

Translated by: Charles T. Ostertag, Jr.

Requester: OLAC PL/STSC/Roger H. Gerzeski

Approved for public release; Distribution unlimited.

Accession For

NTIS CRA&I ☒DTIC TAB ☐Unannounced ☐

Justification

By

Distribution /

Availability Codes

Dist

Avail and/or
Special

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL
FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITO-
RIAL COMMENT STATEMENTS OR THEORIES ADVOC-
ATED OR IMPLIED ARE THOSE OF THE SOURCE AND
DO NOT NECESSARILY REFLECT THE POSITION OR
OPINION OF THE FOREIGN AEROSPACE SCIENCE AND
TECHNOLOGY CENTER.

PREPARED BY:

TRANSLATION DIVISION
FOREIGN AEROSPACE SCIENCE AND
TECHNOLOGY CENTER
WPAFB, OHIO

U. S. BOARD ON GEOGRAPHIC NAMES TRANSLITERATION SYSTEM

Block	Italic	Transliteration	Block	Italic	Transliteration
А а	<i>А а</i>	A, a	Р р	<i>Р р</i>	R, r
В в	<i>В в</i>	B, b	С с	<i>С с</i>	S, s
В в	<i>В в</i>	V, v	Т т	<i>Т т</i>	T, t
Г г	<i>Г г</i>	G, g	У у	<i>У у</i>	U, u
Д д	<i>Д д</i>	D, d	Ф ф	<i>Ф ф</i>	F, f
Е е	<i>Е е</i>	Ye, ye; E, e*	Х х	<i>Х х</i>	Kh, kh
Ж ж	<i>Ж ж</i>	Zh, zh	Ц ц	<i>Ц ц</i>	Ts, ts
З з	<i>З з</i>	Z, z	Ч ч	<i>Ч ч</i>	Ch, ch
И и	<i>И и</i>	I, i	Ш ш	<i>Ш ш</i>	Sh, sh
Й й	<i>Й й</i>	Y, y	Щ щ	<i>Щ щ</i>	Shch, shch
К к	<i>К к</i>	K, k	Ъ ъ	<i>Ъ ъ</i>	"
Л л	<i>Л л</i>	L, l	Ы ы	<i>Ы ы</i>	Y, y
М м	<i>М м</i>	M, m	Ь ь	<i>Ь ь</i>	'
Н н	<i>Н н</i>	N, n	Э э	<i>Э э</i>	E, e
О о	<i>О о</i>	O, o	Ю ю	<i>Ю ю</i>	Yu, yu
П п	<i>П п</i>	P, p	Я я	<i>Я я</i>	Ya, ya

*ye initially, after vowels, and after Ъ, Ь; e elsewhere.
When written as ѣ in Russian, transliterate as ye or ѣ.

RUSSIAN AND ENGLISH TRIGONOMETRIC FUNCTIONS

Russian	English	Russian	English	Russian	English
sin	sin	sh	sinh	arc sh	\sinh^{-1}
cos	cos	ch	cosh	arc ch	\cosh^{-1}
tg	tan	th	tanh	arc th	\tanh^{-1}
ctg	cot	cth	coth	arc cth	\coth^{-1}
sec	sec	sch	sech	arc sch	sech^{-1}
cosec	csc	csch	csch	arc csch	csch^{-1}

Russian English

rot curl
lg log

GRAPHICS DISCLAIMER

All figures, graphics, tables, equations, etc.
merged into this translation were extracted
from the best quality copy available.

METHOD OF DRYING POLYMER PAINT AND VARNISH COATINGS
ON METAL PARTS

(Description of an invention for an author's certificate)

Maksimenko, M.D., Romanovskiy, S.G., Dudnik, M.P.,
and Lifshits, A.I.

(11) 507755

(51) M. Kl.² F 26 B 3/34
B 05 D 3/02

(53) UDC 66.047.354 (088.8)

(22) Date filed 24/12/71

(21) Application number 1727857/24-6

(72) Maksimenko, M.D., Romanovskiy, S.G., Dudnik, M.P.,
and Lifshits, A.I.

(71) Order of Lenin Plant "Leninskaya Kuznitsa" and the Order of Labor
Red Banner Institute of Heat- and Mass-exchange, AS Byelarussian SSR

(54) METHOD OF DRYING POLYMER PAINT AND VARNISH
COATINGS ON METAL PARTS

The invention relates to methods of drying paint and varnish coatings which have been applied on metal parts, and can be used in machine building, ship building, and other branches of industry.

Methods are known for drying paint and varnish coatings on metal parts by means of their inductive heating in an electromagnetic field created by industrial frequency currents.

The purpose of the invention is improving the quality of drying and accelerating the process. For this the heating is carried out at a rate of 30-60°C/h up to a temperature below the break-down temperature of a polymer by 10-15°C with a field strength of 2500-5000 Oe and relative humidity of the surrounding medium of an order of 65-80%, after which the parts undergo isothermal holding for 3-6 h and then are cooled at a rate of 20-40°C.

Items made out of metal or other ferromagnetic material with the paint and varnish coating applied are placed into a chamber which is equipped with a solenoid-type winding made over the entire perimeter of the chamber, in which an electromagnetic field of a specific and same intensity of an order of 2500-5000 Oe is created. The winding is powered with a voltage of 220/380 V of industrial frequency current. When voltage is supplied an electromagnetic field is created, which due to the eddy currents and the effect of remagnetization causes the heating up of the part. The transfer of heat to the coating takes place conductively from the part itself.

The temperature of the part is regulated by changing the magnitude of intensity of the electromagnetic field.

The temperature in the coating is increased at a rate of no more than 60°C an hour and no less than 30°C an hour. The humidity of the medium in the chamber is maintained within the limits of 65-80%, with the help of a vaporizer as an example. Upon achievement of the necessary assigned temperature, which should be 10-15°C lower than the break-down temperature of the polymer in the coating there is isothermic holding for 3-6 h, and then the cooling of the part at a rate of 20-40°C an hour.

The proposed method of drying makes it possible to realize the codirectivity of flows of heat and moisture and to improve the heat- and mass-exchange and the quality of the coating..

Invention Claim

A method of drying polymer paint and varnish coatings on metal parts by means of their inductive heating in an electromagnetic field which is created by industrial frequency currents. Its distinguishing feature is that for the purpose of improving the quality of drying and accelerating the process, the heating is done at a rate of 30-60°C/h up to a temperature which is lower than the polymer break-down temperature by 10-15°C with a field strength of 2500-5000 Oe and relative humidity of the surrounding medium of an order of 65-80%, after which isothermic holding is done for 3-6 h, and then cooling at a rate of 20-40°C/h.

DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

<u>ORGANIZATION</u>	<u>MICROFICHE</u>
B085 DIA/RTS-2FI	1
C509 BALLOC509 BALLISTIC RES LAB	1
C510 R&T LABS/AVEADCOM	1
C513 ARRADCOM	1
C535 AVRADCOM/TSARCOM	1
C539 TRASANA	1
Q592 FSTC	4
Q619 MSIC REDSTONE	1
Q008 NTIC	1
Q043 AFMIC-IS	1
E051 HQ USAF/INET	1
E404 AEDC/DOF	1
E408 AFWL	1
E410 ASDTC/IN	1
E411 ASD/FTD/TTIA	1
E429 SD/IND	1
P005 DOE/ISA/DDI	1
P050 CIA/OCR/ADD/SD	2
1051 AFIT/LDE	1
PO90 NSA/CDB	1
2206 FSL	1

Microfiche Nbr: FTD93C000286L
FTD-ID(RS)T-0244-93